

Canadian Drilling Innovations, Inc.

A Division Of Apex Metal Industries Inc.



156mm (6.125") CVS516UE

IADC S223 (BA-1075)

PRODUCT DETAILS

5 Blade, Steel Bodied Design

Cutters:	(Face)	7 x 13mm (1/2")
	(Face)	12 x 16mm (5/8")
	(Gauge)	5 x 16mm (5/8")
	(Backreamer)	5 x 13mm (1/2")

Nozzles: 5 interchangeable

TFA Range: 1.212 – 6.334 cm²
(0.188 – 0.982 in²)

Gauge length: 6.00" (152.4mm)

Bit connection: 3-1/2" API REG

Min Makeup Torque: 8.5 kNm
(6.3 kft-lb)

Makeup Length: 11.4" (290mm)

Overall length: 14.98" (380mm)

OPERATING PARAMETERS

Flow Rate: 0.75 – 1.7m³/min
(200-450 gpm)

Max Weight on Bit: 9 kdaN (20 klbs)

RPM: Designed for Rotary and Motor

FEATURES

Backreamers, Extended Gauge

Contact Us:

Toll Free: 855-720-7600

Direct : 403-720-7600

Fax: 888-720-3833

E-mail: info@apexmetal.ca



PRODUCT SPECS



Canadian Drilling Innovations, Inc.

A Division Of Apex Metal Industries Inc.



156mm (6.125") CHS513U

IADC S233 (BA-1157)

PRODUCT DETAILS

5 Blade, Steel Bodied Design

Cutters: (Face) 22 x 13mm (1/2")
(Gauge) 4 x 13mm (1/2")
(Gauge) 1 x 11mm (.435")
(Backreamer) 5 x 13mm (1/2")

Nozzles: 5 Interchangeable

TFA Range: 1.581 – 6.334 cm²
(0.245 – 0.982 in²)

Gauge length: 1.25" (32 mm)

Bit connection: 3– 1/2" API REG

Min Makeup Torque: 8.6 kNm
(6.3 kft-lb)

Makeup Length: 6.09" (155 mm)

Overall length: 9.71" (247 mm)

OPERATING PARAMETERS

Flow Rate: 0.75 – 1.7 m³/min
(200-450) gpm

Max Weight on Bit: 9 kdaN (20 klbs)

RPM: Designed for Rotary and Motor

FEATURES

Backreamers

Contact Us:

Toll Free: 855-720-7600

Direct : 403-720-7600

Fax: 888-720-3833

E-mail: info@apexmetal.ca



PRODUCT SPECS

